

Click Safety Adapter Connecting to you

Dual Cone The Embrace of the Nexus can be assembled onto the osseointegration system. With the Interface the Nexus can be connected to a prosthetic of choice.

After placement of the Embrace into the Nexus six spring balls will ensure proper alignment feedback. Allowing to continue by pushing the two safety buttons inwards and then rotate the Secure until a audible safety click. The buttons may then be released.

Your CPO has the freedom to adjust the frontal and the sagittal shift of the prosthetic using Translator 0, 15 or 30 mm. The Translator can rotate around the longitudinal axis of the osseointegration system. Also the Interface is adjustable.

The Nexus has a patented safety slip mechanism. This safety mechanism protects the implant against breaking out from the bone in case of extreme torque forces. When this safety system is activated the Nexus will rotate around the Embrace while remaining fixated in longitudinal direction. By pushing the safety buttons of the Secure the user can realign the prosthesis.

Nexus 0







Nexus 15

Embrace

Secure

Translator

Interface









Nexus 30







Connecting to you



Today's Socket

Losing an extremity is a lifechanging event, resulting in long and heavy rehabilitation trajectories.

Socket disadvantages:

- No anatomical balance
- Limited use of Prosthetic
- Short walking distances
- No sitting comfort
- Skin problems & wounds
- No unity with prosthetic
- Difficult to de- and re-attach

Tomorrow's Osseointegration

Following the introduction of Osseointegration in The Netherlands, we have now developed a Unique Click Safety Adapter serving as a connection (Nexus) between body and prosthetic. With an easy to use and singlehanded quick Secure.





Advantage of the Nexus Click Safety Adapter

- Better sitting position and therefore fewer back problems
- Reduced falling risk due to improved surface feeling
- Equipped with a Unique Dynamic Bounce System
- Fewer skin, wound and transpirations problems
- The prosthesis can easily be put on and off
- Easy to reset Secure & Slip mechanism
- 60° spring ball alignment feedback
- 360° Rotational Translator 0, 15, 30
- Exchangeable 0, 15, 30, Translator
- One Nexus fits right and left
- No Metal on Metal contact
- Longer and better mobility
- Exchangeable Interface
- Secure connection



info@xilloc.com Tel: +31 433 881 881 www.clicksafetyadapter.com

